product details **76123**

Product description: 76123
Product code: 4008321524348
Quantity: Role (ROL) contains 1 Piece (PCE)

You can find this product in the eCatalog:
http://catalog.myosram.com?~language=EN&~country=COM&it_p=4008321524348

Applications	
Dimmable	Yes
Accessories	Control Unit | Remote Control | Connection | Power plug
Adjustable	Yes
Color management (RGB)	Yes
Type of connection	ADHESIVE TAPE

Certificates & Standards	
Standards	CE
Protection against ignition and fire	F, MM
Protection class	II
Type of protection	IP20

General Description	
Number of lighting outlets	1
Equipment	LED
Recycling	Yes
Equipped with lamp	Yes
Body material	EPOXY RESIN
Type of cover	CLEAR

Technical - Colors	
Product color	TRANSPARENT/WHITE

Technical - Electrical Data	
Nominal voltage	12 V
Mains frequency	50 Hz
Nominal current	1.50 A
Nominal wattage	18 W

Technical - Geometries	
Diameter	10 mm
Length	960.00 mm
Width	10.00 mm
Height	2.00 mm

Technical - Light Technical Data	
Luminous intensity	0,866 cd
Luminous flux	98.4 lm
Color rendering index Ra	22.3
Beam angle	113 °

Technical - Temperatures	
Ambient temperature range	...+25 °C

Subject to change without notice. Errors and omission excepted.
© 2011 OSRAM GmbH

Packaging units				
Product code	**Packaging type and content**	**Dimensions in h x w x l**	**Gross weight**	**Volume**
4008321524348	Role contains 1 Piece	100,000 mm x 100,000 mm x 263,000 mm	442,450 g (0,000 g)	2,630 Cubic dec.
4008321524355	Shipping carton box contains 4 Piece	214,000 mm x 297,000 mm x 217,000 mm	2.437,000 g (0,000 g)	13,464 Cubic dec.

LEDs DECO FLEX

Flexible LED strip whose color and color intensity can be changed by remote control. The strip can be cut with scissors to any length so it will fit in any shelving unit and any corner. It is attached by the adhesive strip at the back. The basic set can be easily expanded with the Add-On Kit which contains further strips and connectors.

- CE Sign Protection class II IP20, 12 V, 50 Hz

Subject to change without notice. Errors and omission excepted.
© 2011 OSRAM GmbH